□□□□

SINLOON ® □□□□/□□□

LED Floodlight Power: 600W/750W

Applications





It is suitable for using in parks, hotels, bars, gardens, buildings, lamp posts, playing grounds, stadiums.

Data Spec. 600W 750W

Technical Information	Model No.	Unit	TSC600CW-SC	TSC750CW-SC

Wattage	[W]	600W±5%	750W±5%
Input Voltage	[V]	AC90-305V	AC90-305V
Power Factor	[pF]	≥0.95	≥0.95
Op. Frequency	[Hz]	50/60Hz	50/60Hz
Luminous Flux	[lm]	≥66000lm	≥82500LM
Efficiency	[lm/W]	>110	>110
CRI	[Ra]	>70	>70
CCT	[K]	2700-7000K	2700-7000K
LED Driver(brand)		MOSO DRIVER	MOSO DRIVER
Output Voltage	[V]	20-54V	20-54V
Output Current	[mA]	4200mA±3%	4200mA±3%*2
Kind of LED	[SMD]	8 x COB	10 x COB
Brand of LED Chip		SAN'AN	SAN'AN
Beam Angle		30°/60°/120°	30°/60°/120°
Average Life	[hrs]	50000	50000
Maintenance Luminous Flux 70%	[hrs]	50000	50000
Ta - Working Ambinet Temp.	[ºC]	-40□ to +60□	-40□ to +60□
Tc - Working Temperature	[ºC]	+90□	+90□
IP - Index Protection	IP	IP65	IP65

Reflector Material			-	-
Difusor Material			PC	PC
Body Material			stretching Alu.	stretching Alu.
Weight		[Kg]	15.4kgs	17.8kgs
Dimensions of Product (L x W x H)		[mm]	490*475*128 mm	490*598*128 m
Certificates			RoHS/CE	RoHS/CE
Warranty by Supplier			2 Years	2 Years
Inner	Kind of Packing		white box	white box
Barcode			-	-
Dimension (L x W xH)		[mm]	520*520*220 mm	520*620*220 m
Pcs/Ctn		Un/Cx	1pc/Cx	1pc/Cx
Outer	Kind of Packing		Export carton Packing	Export carton Packing

LED Floodlight - TCS600W TSC750W
最近更新 週一 , 09 一月 2017 06:49

Barcode	-	-	
Weight	[kg]	16.4kgs	19kgs
Dimension (L x W x H)	[mm]	520*520*220 mm	520*620*220 m
Pcs/Ctn	Un/Cx	1pc/Ctn	1pc/Ctn

Return

在本規格書裡如果您未能找到或參數指標未能達到你的應用要求即未在本規格書裡表現出來請與我們聯絡 .

6 / 6