

低阻值厚膜貼片電阻

THICK FILM LOW OHM CHIP RESISTORS

RATINGS

TYPE	Power Rating at 70°C	Rate Current Voltage(Vr)	Max Working Voltage(Vw)	Max Over Load Voltage(Vo)	TCR (PPM/°C)	Resistance Tolerance (%)	Resistance Range (Ω)	Operating Temperature (°C)
0402	0.0625 W	0.13 V~0.86 V	0.43 V	0.86 V	± 800	±1%	0.1~0.99	-55°C~+125°C
					±1500	±5%	0.1~0.99	
0603	0.1 W	0.17 V~1.09 V	0.54 V	1.08 V	± 800	±1%	0.01~0.99	-55°C~+125°C
					±1500	±5%	0.01~0.99	
0805	0.125 W	0.19 V~1.22 V	0.61 V	1.22 V	± 800	±1%	0.01~0.99	-55°C~+125°C
					±1500	±5%	0.01~0.99	
1206	0.25 W	0.27 V~1.74 V	0.87 V	1.74 V	± 800	±1%	0.01~0.99	-55°C~+125°C
					±1500	±5%	0.01~0.99	
1210	0.33 W	0.31 V~1.98 V	0.99 V	1.98 V	± 800	±1%	0.01~0.99	-55°C~+125°C
					±1500	±5%	0.01~0.99	
2010	0.5 W	0.38 V~2.44 V	1.22 V	2.44 V	± 800	±1%	0.01~0.99	-55°C~+125°C
					±1500	±5%	0.01~0.99	
2512	1.0 W	0.54 V~3.46 V	1.73 V	3.46 V	± 800	±1%	0.01~0.99	-55°C~+125°C
					±1500	±5%	0.01~0.99	

高阻值厚膜貼片電阻

THICK FILM HIGH OHM CHIP RESISTORS**RATINGS**

TYPE	Power Rating at 70°C	Max Working Voltage(Vw)	Max Over Load Voltage(Vo)	TCR (PPM/°C)	Resistance Tolerance (%)	Resistance Range (Ω)	Operating Temperature (°C)
0402	0.0625 W	50 V	100 V	±200	±1%	10.1M~54M	-55°C~+125°C
					±5%	10.1M~100M	
					±10%	10.1M~100M	
0603	0.1 W	50 V	100 V	±200	±1%	10.1M~54M	-55°C~+125°C
					±5%	10.1M~100M	
					±10%	10.1M~100M	
0805	0.125 W	150 V	300 V	±200	±1%	10.1M~54M	-55°C~+125°C
					±5%	10.1M~100M	
					±10%	10.1M~100M	
1206	0.25 W	200 V	400 V	±200	±1%	10.1M~54M	-55°C~+125°C
					±5%	10.1M~100M	
					±10%	10.1M~100M	
1210	0.33 W	200 V	400 V	±200	±1%	10.1M~54M	-55°C~+125°C
					±5%	10.1M~100M	
					±10%	10.1M~100M	
2010	0.5 W	200 V	400 V	±200	±1%	10.1M~54M	-55°C~+125°C
					±5%	10.1M~100M	
					±10%	10.1M~100M	
2512	1.0 W	200 V	400 V	±200	±1%	10.1M~54M	-55°C~+125°C
					±5%	10.1M~100M	
					±10%	10.1M~100M	