

SINLOON®

LED 投光燈 (大功率)
LED Floodlight High power

SV-TG18 Series
Power : 100W/150W/200W

Hong Kong Brand

Feature:

Length Dimension: Standard
Case material: Metal aluminum + tempered glass
Lumen: 65-75lm/W
On lighting: Transient to start
Input voltage: AC85~260V 50/60Hz
Light source: LED SMD2835 chip diode
Shine: To product light not flashing
LEDs Lifespan: 25,000hrs

SV-TG18 Series



Characteristic Parameters:

型號 Model No.:	SV-TG18-100W	SV-TG18-150W	SV-TG18-200W
尺寸 Dimension (L*Φ): Φ/Circular Type	255*75*285mm	245*80*310mm	380*97*349
輸入電壓 Input Voltage:	AC85V~260V 50/60Hz	AC85V~260V 50/60Hz	AC85V~260V 50/60Hz
輸出電流 Output Current:	280mA	280mA	280mA
類型 LED Type:	COB	COB	COB
數量 LED Quantity:	2 pcs	3 pcs	4 pcs
功率 System Power (W)	100W±5%	150W±5%	200W±5%
光通亮 LED Flux (lm) /	8000lm ±5%	12000lm ±5%	13700lm ±5%
燈罩 Frost cover	Tempered glass	Tempered glass	Tempered glass
功率係數 Power Factor:	>0.95	>0.95	>0.95
色溫 Color Temperature (K)	3000K ±7% / 6500K ±8%	3000K ±7% / 6500K ±8%	3000K ±7% / 6500K ±8%
顯色指數 Color Rendering Index:	>75Ra	>75Ra	>75Ra
發光角度 Illumination Angle:	120°	120°	120°
燈源壽命 LEDs Lifespan:	25000hrs	25000hrs	25000hrs
環境溫度 Ambient Temperature (°C):	-20°C ~ 50°C		
認證 Certificate:	CE/IP66		
外殼材質 Outer material:	金屬鋁+鋼化玻璃 (Metal aluminum + tempered glass) 黑色/Black Color		

Superiority (優勢):

○ 採用台灣高亮度LED芯片光源, 抗震, 耐衝擊.

Using high brightness LED chip imported from Taiwan Shock and impact resistant.

○ 無熱輻射, 安全穩定, 可靠, 使用壽命長, 款式新穎.

No thermal radiation, security and stability, reliable, long life and fashionable style.

○ 響應快, 無頻閃, 眩光小, 點亮後瞬間達到全光通量輸出.

Fast response, No flash, Low glare, Lightening instantly reach the luminous flux output.

○ 採用優質擴光罩, 光色柔和, 出光率高

Use the high quality frosted PC, Soft light and the high light extracting Rate.

○ 節能高效, 比螢光燈節能70%.

High efficiency and energy saving, Saved more than 70% power compare with conventional fluorescent light.



*在本規格書裡如果您未能找或參數指標未能達到你的應用要求即未在本規格書裡表現出來請與我們聯絡.

* If you have any question which is not is in the specification, please contact us.