

SINLOON® 聚光射燈/泛光燈
LED Floodlight

TSC series
Power: 150W/180W

■ Applications

It is suitable for using in parks, hotels, bars, gardens buildings, lamp posts, playing grounds, stadiums.



■ Data Specification

Technical Information	Model No.	Unit	TSC150CW-SE	TSC180CW-SE
	Wattage	[W]	150W±5%	180W±5%
	Input Voltage	[V]	AC100-240V	AC100-240V
	Power Factor	[pF]	≥0.95	≥0.95
	Op. Frequency	[Hz]	50/60Hz	50/60Hz
	Luminous Flux	[lm]	≥16500LM	≥19800LM
	Efficiency	[lm/W]	>110	>110
	CRI	[Ra]	>70	>70
	CCT	[K]	2700-7000K	2700-7000K
	LED Driver(brand)		MOSO	MOSO
	Output Voltage	[V]	20-54V	20-54V
	Output Current	[mA]	4200mA±3%*2	6300mA±3%*2
	Kind of LED	[SMD]	3 x COB	3 x COB
	Brand of LED Chip		SAN'AN	SAN'AN
	Beam Angle		30°/60°/120°	30°/60°/120°
	Average Life	[hrs]	50000	50000
	Maintenance Luminous Flux	[hrs]	50000	50000
	Ta - Working Ambient Temp.	[°C]	-40°C to +60°C	-40°C to +60°C
	Tc - Working Temperature	[°C]	+90°C	+90°C
	IP - Index Protection	IP	IP65	IP65
Reflector Material		-	-	
Difusor Material		PC	PC	
Body Material		stretching Alu.	stretching Alu.	
Weight	[Kg]	6.7kgs	6.9kgs	
Dimensions of Product (L x W x H)	[mm]	547*230*232.5 mm	547*230*232.5 mm	
Certificates		RoHS/CE	RoHS/CE	
Warranty by Supplier		2 Years	2 Years	
Inner	Kind of Packing		white box	white box
	Barcode		-	-
	Dimension (L x W xH)	[mm]	447*232*232.5 mm	447*232*232.5 mm
	Pcs/Ctn	Un/Cx	1pc/Cx	1pc/Cx
Outer	Kind of Packing		Export carton Packing	Export carton Packing
	Barcode		-	-
	Weight	[kg]	7.2kgs	7.4kgs
	Dimension (L x W x H)	[mm]	580*330*195 mm	580*330*195 mm
	Pcs/Ctn	Un/Cx	1pc/Ctn	1pc/Ctn

在本規格書裡如果您未能找到或參數指標未能達到你的應用要求即未在本規格書裡表