

SINLOON®

聚光射燈/泛光燈
LED Floodlight

TSC series

Power: 200W/240W

■ Applications

It is suitable for using in parks, hotels, bars, garden buildings, lamp posts, playing grounds, stadiums.



■ Data Specification

	Model No.	TSC200CW-SE		TSC240CW-SE	
Technical Information	Wattage	[W]	200W±5%	240W±5%	
	Input Voltage	[V]	AC100-240V	AC100-240V	
	Power Factor	[pF]	≥0.95	≥0.95	
	Op. Frequency	[Hz]	50/60Hz	50/60Hz	
	Luminous Flux	[lm]	≥22000lm	≥26400LM	
	Efficiency	[lm/W]	>110	>110	
	CRI	[Ra]	>70	>70	
	CCT	[K]	2700-7000K	2700-7000K	
	LED Driver(brand)		MOSO	MOSO	
	Output Voltage	[V]	20-54V	20-54V	
	Output Current	[mA]	6300mA±3%*2	7500mA±3%*2	
	Kind of LED	[SMD]	4 x COB	4 x COB	
	Brand of LED Chip		SAN'AN	SAN'AN	
	Beam Angle		30°/60°/120°	30°/60°/120°	
	Average Life	[hrs]	50000	50000	
	Maintenance Luminous Flux	[hrs]	50000	50000	
	Ta - Working Ambient Temp.	[°C]	-40°C to +60°C	-40°C to +60°C	
	Tc - Working Temperature	[°C]	+90°C	+90°C	
	IP - Index Protection	IP	IP65	IP65	
	Reflector Material		-	-	
Difusor Material		PC	PC		
Body Material		stretching Alu.	stretching Alu.		
Weight	[Kg]	7.0kgs	7.5kgs		
Dimensions of Product (L x W x H)	[mm]	547*230*232.5 mm	547*230*232.5 mm		
Certificates		RoHS/CE	RoHS/CE		
Warranty by Supplier		2 Years	2 Years		
Inner	Kind of Packing		white box	white box	
	Barcode		-	-	
	Dimension (L x W x H)	[mm]	580*330*195 mm	580*330*195 mm	
	Pcs/Ctn	Un/Cx	1pc/Cx	1pc/Cx	
Outer	Kind of Packing		Export carton Packing	Export carton Packing	
	Barcode		-	-	
	Weight	[kg]	8.0kgs	8.6kgs	
	Dimension (L x W x H)	[mm]	580*330*195 mm	580*330*195 mm	
	Pcs/Ctn	Un/Cx	1pc/Ctn	1pc/Ctn	

在本規格書裡如果您未能找到或參數指標未能達到你的應用要求即未在本規格書裡表現出來請與我們聯絡。