

SINLOON®

聚光射燈/泛光燈
LED Floodlight

XGH series

Power: 30W/50W

■ Applications

It is suitable for using in parks, hotels, bars, gardens, buildings, lamp posts, playing grounds, stadiums.



■ Data Specification

Technical Information	Model No.		XGH30CW-SA	XGH50CW-SA
	Wattage	[W]	30W±5%	50W±5%
	Input Voltage	[V]	AC170-265V	AC170-265V
	Power Factor		≥0.5	≥0.9
	Op. Frequency	[Hz]	50/60Hz	50/60Hz
	Luminous Flux	[lm]	≥3000LM	≥5000LM
	Efficiency	[lm/W]	>100	>100
	CRI	[Ra]	>70	>70
	CCT	[K]	2700-7000K	2700-7000K
	LED Driver(brand)		RAYSHINE DRIVER	RAYSHINE DRIVER
	Output Voltage	[V]	24-36V	24-36V
	Output Current	[mA]	800mA±3%	1300mA±3%
	Kind of LED	[SMD]	SMD2835*30	SMD2835*48
	Brand of LED Chip		SAN'AN	SAN'AN
	Beam Angle		120°	120°
	Average Life	[h]	50000	50000
	Maintenance Luminous Flux	[h]	50000	50000
	Ta - Working Ambient Temp.	[°C]	-40°C to +60°C	-40°C to +60°C
	Tc - Working Temperature	[°C]	+65°C	+65°C
	IP - Index Protection	IP	IP65	IP65
Reflector Material		-	-	
Difusor Material		PC	PC	
Body Material		stretching Alu.	stretching Alu.	
Weight	[Kg]	0.708kgs	0.987kgs	
Dimensions of Product (L x W x H)	[mm]	144*138*63 mm	190*138*63 mm	
Certificates		RoHS/CE	RoHS/CE	
Warranty by Supplier		2 Years	2 Years	
Inner	Kind of Packing		white box	white box
	Barcode		-	-
	Dimension (L x W x H)	[mm]	180*175*165 mm	230*175*165 mm
Outer	Pcs/Ctn	Un/Cx	2pc/Cx	2pc/Cx
	Kind of Packing		Export carton Packing	Export carton Packing
	Barcode		-	-
	Weight	[kg]	18.4kgs	17.8kgs
	Dimension (L x W x H)	[mm]	565*365*350 mm	565*365*350 mm
Pcs/Ctn	Un/Cx	24pc/Ctn	16pc/Ctn	

在本規格書裡如果您未能找到或參數指標未能達到你的應用要求即未在本規格書裡表現出來請與我們聯絡。