

Feature:

- Frame measurement Standard size.
- Frame material: Aluminum metal
- Voltage Type: Constant current (External adaptor)
- Temperature Color: White
- Input voltage: AC110~240V 50/60Hz
- Light source: LED SMD5630 type
- Shine: To product light not flashing
- Framework: Arc angle shaped
- Panel: Ultra-thin guiding light, Energy conservation

Figure




Characteristic Parameters:

型號 Model No.:		MLL-A4568S (Single Panel)
尺寸 Dimension (L*W*T):		455*685*11.2mm
發光尺寸 The Emitting Size:		405*635mm
輸入電壓(外置電源) Input Voltage (External Adaptor):		AC110V~240V 50/60Hz
輸出電壓 Output Voltage: (AC/DC Adaptor)		32V DC
電流 Current:		1.5A
類型 LED Type:		SAMSUNG LED - SMD5630
數量 LED Quantity:		120pcs
功率 System Power (W)		54W ±5%
亮度 Brightness (on the surface panel)		15000 Lux
色溫 Color Temperature (K)		Color: White 6000K ±8%
顯色指數 Color Rendering Index:		80±2
發光角度 Illumination Angle:		120°
壽命 Lifespan:		40000hrs (25°C)
環境溫度 Ambient Temperature (C):		-20°C ~ 50°C
重量 Weight (Kg):		<6.5/kg
認證 Certificate:		BSMI/CE/RoHS/FCC

* If you have any question which is not in the specification, please contact us.

*在本規格書裡如果您未能找到或參數指標未能達到你的應用要求即未在本規格書裡表現出來請與我們聯絡。

Dimension:



Think (T): Double Panel: 16.5mm
 Single Panel: 11.2mm
 Frame: wide: 30mm



* If you need others special frame size, please contact us.

(如需要其它特殊框架尺寸請與我們聯絡)。

A4568 (54W)