

SINLOON®

聚光射燈/泛光燈

LED Floodlight

TSC series

Power: 600W/750W

■ Applications

It is suitable for using in parks, hotels, bars, gardens buildings, lamp posts, playing grounds, stadiums.



■ Data Specification

	Model No.	Unit	TSC600CW-SC	TSC750CW-SC
	Technical Information	Wattage	[W]	600W±5%
Input Voltage		[V]	AC90-305V	AC90-305V
Power Factor		[pF]	≥0.95	≥0.95
Op. Frequency		[Hz]	50/60Hz	50/60Hz
Luminous Flux		[lm]	≥66000lm	≥82500LM
Efficiency		[lm/W]	>110	>110
CRI		[Ra]	>70	>70
CCT		[K]	2700-7000K	2700-7000K
LED Driver(brand)			MOSO DRIVER	MOSO DRIVER
Output Voltage		[V]	20-54V	20-54V
Output Current		[mA]	4200mA±3%	4200mA±3%*2
Kind of LED		[SMD]	8 x COB	10 x COB
Brand of LED Chip			SAN'AN	SAN'AN
Beam Angle			30°/60°/120°	30°/60°/120°
Average Life		[hrs]	50000	50000
Maintenance Luminous Flux		[hrs]	50000	50000
Ta - Working Ambient Temp.		[°C]	-40°C to +60°C	-40°C to +60°C
Tc - Working Temperature		[°C]	+90°C	+90°C
IP - Index Protection		IP	IP65	IP65
Reflector Material			-	-
Difusor Material			PC	PC
Body Material			stretching Alu.	stretching Alu.
Weight		[Kg]	15.4kgs	17.8kgs
Dimensions of Product (L x W x H)		[mm]	490*475*128 mm	490*598*128 mm
Certificates			RoHS/CE	RoHS/CE
Warranty by Supplier			2 Years	2 Years
Inner	Kind of Packing		white box	white box
	Barcode		-	-
	Dimension (L x W xH)	[mm]	520*520*220 mm	520*620*220 mm
	Pcs/Ctn	Un/Cx	1pc/Cx	1pc/Cx
Outer	Kind of Packing		Export carton Packing	Export carton Packing
	Barcode		-	-
	Weight	[kg]	16.4kgs	19kgs
	Dimension (L x W x H)	[mm]	520*520*220 mm	520*620*220 mm
	Pcs/Ctn	Un/Cx	1pc/Ctn	1pc/Ctn

在本規格書裡如果您未能找到或參數指標未能達到你的應用要求即未在本規格書裡表現出來請與我們聯絡。