

SINLOON®

聚光射燈/泛光燈
LED Floodlight

TSC series
Power: 900W

■ Applications

It is suitable for using in parks, hotels, bars, gardens buildings, lamp posts, playing grounds, stadiums.



■ Data Specification

Technical Information	Model No.	Unit	TSC900CW-SC
	Wattage	[W]	900W±5%
	Input Voltage	[V]	AC90-305V
	Power Factor	[pF]	≥0.95
	Op. Frequency	[Hz]	50/60Hz
	Luminous Flux	[lm]	≥99000LM
	Efficiency	[lm/W]	>110
	CRI	[Ra]	>70
	CCT	[K]	2700-7000K
	LED Driver(brand)		MOSO DRIVE
	Output Voltage	[V]	20-54V
	Output Current	[mA]	4200mA±3%
	Kind of LED	[SMD]	12 x COB
	Brand of LED Chip		SAN'AN
	Beam Angle		30°/60°/120°
	Average Life	[hrs]	50000
	Maintenance Luminous Flux	[hrs]	50000
	Ta - Working Ambient Temp.	[°C]	-40°C to +60°C
	Tc - Working Temperature	[°C]	+90°C
	IP - Index Protection	IP	IP65
	Reflector Material		-
	Difusor Material		PC
	Body Material		stretching Alu.
	Weight	[Kg]	21.3kgs
	Dimensions of Product (L x W x H)	[mm]	490*720*128 mm
Inner	Certificates		RoHS/CE
	Warranty by Supplier		2 Years
	Kind of Packing		white box
	Barcode		-
Outer	Dimension (L x W xH)	[mm]	520*720*220mm
	Pcs/Ctn	Un/Cx	1pc/Cx
	Kind of Packing		Export carton Packing
	Barcode		-
	Weight	[kg]	23kgs
	Dimension (L x W x H)	[mm]	520*720*220mm
	Pcs/Ctn	Un/Cx	1pc/Ctn

在本規格書裡如果您未能找到或參數指標未能達到你的應用要求即未在本規格書裡表現出來請與我,