

SINLOON®

明裝筒燈導光板LED照明(RD)系列

MLL-RD120-6W

LED Circular Guide Panel Light (RD) Series

MLL-RD-172-12W

Feature:

Frame measurement:	Standard size.	(標準尺寸)
Frame material:	Metal	(注塑外殼)
Voltage Type:	External Adaptor	(外置電源)
Ambient Light:	Instant start	(片刻啟動)
Input voltage:	AC220~240V 50/60Hz	(市電電壓)
LED Light source:	LED SMD3014 chip diode	(3014燈源)
Shine:	To product light not flashing	(無頻閃)
Fixing Way:	Ceiling	(掛頂式)

Figure:



Characteristic Parameters:

型號 Model No.:	MLL-RD120-6W	MLL-RD172-12W
尺寸 Dimension (D):	Φ120*35mm	Φ172*35mm
發光尺寸 The Emitting Size (d):	Φ80mm	Φ132mm
輸入電壓(外置電源) Input Voltage (External Adaptor):	AC110V~240V 50/60Hz	AC110V~240V 50/60Hz
輸出電壓 Output Voltage (AC/DC Adaptor):	54-84VDC	54-84VDC
電流 Current:	94mA	187mA
類型 LED Type:	SMD2835	SMD2835
數量 LED Quantity:	30pcs	60pcs
功率/亮度 System Power (W) / Lux/2M:	6W ±5%	12W ±5%
光通亮 LED Flux (lm):	390lm ±15%	860lm ±15%
燈具效率 Lighting Factor:	60%	70%
功率系數 Power Factor:	>0.9	>0.9
色溫 Color Temperature (K):	3000K ±7% / 7000K ±8%	3000K ±7% / 7000K ±8%
顯色指數 Color Rendering Index:	>75	>75
發光角度 Illumination Angle:	120°	120°
壽命 Lifespan:	50000hrs	50000hrs
環境溫度 Ambient Temperature (°C):	-20°C ~ 50°C	-20°C ~ 50°C
重量 Weight (Kg):	<0.4/kg	<0.6/kg

\* If you have any question which is not in the specification, please contact us.

\*在本規格書裡如果您未能找到或參數指標未能達到你的應用要求即未在本規格書裡表現出來請與我們聯絡。

Figure: Back



\* If you need others special frame size, please contact us.

(如有需要其它特殊尺寸請與我們聯絡。)