


Data Specification:

市場用途:

商場店舖; 酒店; 飾櫃; 展示櫃等。




Performance	Product Model:	OT-3430-23W	OT-3430-33W	OT-3430-40W
Performance parameter	Lamp	Warm white / Natural white / Cool white (暖白/自然白/冷白)		
	Lumen (lm)	1300lm/1400lm/1500lm	1850lm/1950lm/2000lm	2400lm/2500lm/2600lm
	Color temperature (K)	3000K / 4200K / 6500K	3000K / 4000K / 6000K	3000K / 4000K / 5000K
	CRI	≥80	≥80	≥80
	Type of LED	COB LED	COB LED	COB LED
	Beam angle	25°	25°	25°
	Decay rate (%)	Less than 3% within 1000 working hours		
	Total power (W)	23-25W	34-36W	42-46W
	Lifespan (Hrs)	≥30000Hrs	≥30000Hrs	≥30000Hrs
	High voltage testing	1750Vac/1min	1750Vac/1min	1750Vac/1min
LED Parameter	Lighting efficiency	100lm/W	100lm/W	100lm/W
	Chip quantity	48 Pcs	54 Pcs	54 Pcs
	Series-parallel way	12S4P	12S7P	12S7P
	Voltage	37VDC	37VDC	37VDC
	Current	600mA	900mA	1050mA
Driver Parameter	Input parameter	100~240VAC, 50/60Hz		
	Power factor	0.9	0.9	0.9
	Output parameter	30-37VDC,600mA	30-40VDC,900mA	30-40VDC,1050mA
Structure Parameter	Material	Aluminium	Aluminium	Aluminium
	Deimension	156*60*223mm	156*68*223mm	156*68*223mm
	Cut-out	/	/	/
	Protection class	calss I	calss I	calss I
	IP	IP20	IP20	IP20
Environment Parameter	Application	Hotel、Home-lighting、Recreation place、Supermarket、Office building		
	Operating temperature	-25℃ ~ 50℃、10% ~ 90% R.H.		
	Storage temperature	-30℃ ~ 85℃、0% ~ 95% R.H.		
Packing Specification	Q'ty. / Weight:	12 pcs / Ctns	12 pcs / Ctns	12 pcs / Ctns
	Carton Size:	31.5x31.5x37.5 cm	31.5x31.5x37.5 cm	31.5x31.5x37.5 cm




OT-3430-23W



OT-3430-33W



OT-3430-40W



* Others data not in the specification of data, please contact us.

如果你要求的規格參數未在本規格書裡表現出來請與我們聯絡。