


## Data Specification:

市場用途:


商場店舖; 酒店; 飾櫃; 展示櫃等。




Performance	Prodct Model:	OT-3730-10W	OT-3740-20W	OT-3750-30W			
Performance parameter	Lamp	Warm white / Natural white / Cool white (暖白/自然白/冷白)					
	Lumen (lm)	550 lm / 570 lm / 600lm	1100lm/1220lm/1300lm	1550lm/1650lm/1780lm			
	Color temperature (K)	3000K / 4200K / 6500K					
	CRI	≥70	≥70	≥70			
	Type of LED	COB LED	COB LED	COB LED			
	Beam angle	65°	67.8°	68°			
	Decay rate (%)	Less than 3% within 1000 working hours					
	Total power (W)	10-11W	20-22W	31-34W			
	Lifespan (Hrs)	≥30000Hrs	≥30000Hrs	≥30000Hrs			
	High voltage testing	1750Vac/1min	1750Vac/1min	1750Vac/1min			
LED Parameter	Lighting efficiency	100LM/W	100LM/W	100LM/W			
	Chip quantity	50 Pcs	96 Pcs	144 Pcs			
	Series-parallel way	5S10P	12S8P	12S12P			
	Voltage	15-17VDC	37-39VDC	37-39VDC			
	Current	550mA	550mA	850mA			
Driver Parameter	Input parameter	100~240VAC · 50/60Hz					
	Power factor	0.8	0.9	0.9			
	Output parameter	18-24VDC,550mA	24-49VDC,550mA	24-44VDC,550mA			
Structure Parameter	Material	Aluminium	Aluminium	Aluminium			
	Deimension	145*114*196mm	158*141*239mm	182*173*264mm			
	Cut-out	/	/	/			
	Protection class	calss I	calss I	calss I			
	IP	IP20	IP20	IP20			
Environment Parameter	Application	Hotel、Home-lighting、Recreation place、Supermarket、Office building					
	Operating temperature	-25℃ ~ 50℃、10% ~ 90% R.H.					
	Storage temperature	-30℃ ~ 85℃、0% ~ 95% R.H.					
Packing Specification	Q'ty. / Weight:	20 pcs	4/6kg	20 pcs	8/10Kg	10 pcs	6/8kg
	Carton Size:	28.5x28x50 cm		31.5x31.5x52.5 cm			




OT-3730-10W



OT-3740-20W



OT-3750-30W



\* Others data not in the specification of data, please contact us.

如果你要求的規格參數未在本規格書裡表現出來請與我們聯絡。