



Data Specification:

市場用途:



商場店舖; 酒店; 飾櫃; 展示櫃等.



Performance	Product Model:	OT-4230-30W	OT-4230-33W
Performance parameter	Lamp	Warm white / Natural white / Cool white (暖白/自然白/冷白)	
	Lumen (lm)	1200lm/1250lm/1300lm	550 lm / 570 lm / 600lm
	Color temperature (K)	3000K/4000K/5000K	3000K / 4200K / 6500K
	CRI	≥80	≥80
	Type of LED	COB LED	COB LED
	Beam angle	24°	65°
	Decay rate (%)	Less than 3% within 1000 working hours	
	Total power (W)	23-24W	10-11W
	Lifespan (Hrs)	≥30000Hrs	≥30000Hrs
	High voltage testing	1750Vac/1min	1750Vac/1min
LED Parameter	Lighting efficiency	100LM/W	100LM/W
	Chip quantity	48 Pcs	50 Pcs
	Series-parallel way	12S4P	5S10P
	Voltage	37VDC	15-17VDC
	Current	600mA0	550mA
Driver Parameter	Input parameter	100~240VAC , 50/60Hz	100~240VAC , 50/60Hz
	Power factor	0.9	0.8
	Output parameter	30-37VDC,600mA	18-24VDC,550mA
Structure Parameter	Material	Aluminium	Aluminium
	Deimension	145*110*195mm	145*114*195mm
	Cut-out	/	/
	Protection class	calss I	calss I
	IP	IP20	IP20
Environment Parameter	Application	Hotel 、 Home-lighting 、 Recreation place 、 Supermarket 、 Office building	
	Operating temperature	-25℃ ~ 50℃ 、 10% ~ 90% R.H.	
	Storage temperature	-30℃ ~ 85℃ 、 0% ~ 95% R.H.	
Packing Specification	Q'ty. / Weight:	8 pcs/Ctns	
	Carton Size:		



OT-4230-30W



OT-4230-33W

* Others data not in the specification of data, please contact us.

如果你要求的規格參數未在本規格書裡表現出來請與我們聯絡。