

SINLOON®

T5 LED 燈管
T5 LED Tube Series

型號類別 T5B series

玻璃管

T5 Glass LED Tube (Plastic End cap.)

Hong Kong Brand

Feature:

Length Dimension: Standard size.
Case material: Glass cover + Plastic end cap
Driver IC
Lumen: 100lm/W
On lighting: Transient to start
Input voltage: AC180~260V 50/60Hz
Light source: LED SMD2835 chip diode
Shine: To product light not flashing
LEDs Lifespan: 25,000hrs

T8 LED Tube Figure



AC Input Double End Virsion

Characteristic Parameters:

型號 Model No.:	XGYT5102-E9	XGYT5104-E18
尺寸 Dimension (L*Φ): Φ/Circular Type	Φ16*600mm	Φ16*1200mm
實際長度 Actual Length Size:	599mm	1199mm
鋁基板寬度 PCB width :	8.0mm	8.0mm
輸入電壓 Input Voltage: (Double End Virsion)	AC180V~265V 50/60Hz	AC180V~260V 50/60Hz
類型 LED Type:	SMD2835	SMD2835
數量 LED Quantity:	48pcs	96pcs
功率 System Power (W)	9.0W±5%	18W±5%
光通亮 LED Flux (lm) /	900lm ±5%	1800lm ±5%
燈罩 Frost cover	Translucent	Translucent
功率系數 Power Factor:	>0.5	>0.5
色溫 Color Temperature (K)	3000K ±7% / 6500K ±8%	3000K ±7% / 6500K ±8%
顯色指數 Color Rendering Index:	>80Ra	>80Ra
發光角度 Illumination Angle:	320°	320°
燈源壽命 LEDs Lifespan:	25000hrs	25000hrs
環境溫度 Ambient Temperature (°C):	-20°C ~ 50°C	
認證 Certificate:	RoHS	

Superiority (優勢):

○ 採用台灣高亮度LED芯片光源, 抗震, 耐衝擊。

Using high brightness LED chip imported from Taiwan Shock and impact resistant.

○ 無熱輻射, 安全穩定, 可靠, 使用壽命長, 款式新穎。

No thermal radiation, security and stability, reliable, long life and fashionable style.

○ 響應快, 無頻閃, 眩光小, 點亮後瞬間達到全光通量輸出。

Fast response, No flash, Low glare, Lightening instantly reach the luminous flux output

○ 採用優質擴光罩, 光色柔和, 出光率高

Use the high quality frosted PC, Soft light and the high light extracting Rate.

○ 節能高效, 比螢光燈節能70%。

High efficiency and energy saving, Saved more than 70% power compare with conventional fluorescent light.



*在本規格書裡如果您未能找或參數指標未能達到你的應用要求即未在本規格書裡表現出來請與我們聯絡。

* If you have any question which is not is in the specification, please contact us.

SINLOON®