

SINLOON®

緊湊型一體無極燈

Compact Induction Lamp

Model No. MLL-YD Series

Lifetime: 60,000hrs

■ Feature:

- Power Range: 20W ~ 50W
- Efficiency: 50~65lm/W
- The Lifetime: 60,000 hrs
- Ambient Light: Instant start
- Shine: Not flashing
- Lighting Direct.: Arbitrary

■ Figure: YD



■ Order information:

Example: Model + Holder Base  
MLL-YD20E27

■ Characteristic Parameters:

型號	功率	電壓	光通量	顏色	光效	顯色指數	工作頻率	有效光效
Model	Power *	Voltage (V)	(lm)	Color Temp.	lm/W	CRI (Ra)	Frequency MHz	PLM/W
MLL-YD-20	20W	120/220/277	1000-1200	2700K-6500K	50-60/W	≥80	2.65±2	83-100/W
MLL-YD-30	30W	120/220/277	1560-1800	2700K-6500K	50-60/W	≥80	2.65±2	83-100/W
MLL-YD-40	40W	120/220/277	2200-2600	2700K-6500K	55-65/W	≥80	0.23±30	98-115/W
MLL-YD-50	50W	120/220/277	2700-3500	2700K-6500K	55-65/W	≥80	0.23±30	98-139/W
The lamp holder base	燈頭類型:		E14/E27/E40.					
Temperature	環境溫度:		-25 ~ +50°C					
Lifetime	使用壽命		60000hrs					

Power \* : The power means the lamp power and the high-frequency generator and power.

(\* :指功率和高頻發生器功率之和)

◆ Characteristic parameters of electronic product specification change or updates without prior notice.

(注意: 產品參數的任何改變和更新不會另行通知)

■ Application:

- Playground (操場)
- Shop market (商場)
- Supermarket (超市商店)
- Lobby (大堂)
- Large building (高樓大廈)
- Tunnels (隧道)
- Road (路燈)
- Etc. (等等)



◆ If you have any question which is in the specification , please contact us.

(在本規格書裡如果您未能找到或參數指標未能達到你的應用要求即未在本規格書裡表現出來請與我們聯絡。)