

SINLOON®

## 貼片型穩壓二極管

### Surface Mount Zener Diode

SZD55C - 0805/1206

Voltage Range: 0.5W 4.7V ~ 36V (±5%)

#### Features

- ◆ Surface mount device, suitable for auto-placement surface mounting application
- ◆ Metal tin plating termination layer for fellow & wave soldering
- ◆ Silicon Planar Power Zener Diode.
- ◆ ±5%, ±2% standard Vz Tolerance
- ◆ 4.7V ~ 36 Nominal Zener Voltage
- ◆ Designed for Surface Mount Application

#### Mechanical Data

- ◆ Case: 0805 Weight approx 6 mg
- 1206 Weight approx 10 mg
- ◆ Marking Cathode band
- ◆ Mounting Position: Any


ORDERING INFORMATION See page 2 of Part number  
Example: SZD55C4V7S (0805 4.7V)

| Type | Diode | Tolerance        | Voltage   | Size             |
|------|-------|------------------|-----------|------------------|
| SZD  | 55    | C: ±5%<br>B: ±2% | 4V7 ~ 36V | S : 0805<br>1206 |

#### Figure





#### Device Marking



#### DIMENSION

Unit: mm

| Type     | Size | DIMENSION |          |          |          |          | Mounting Pad Layout |      |     |
|----------|------|-----------|----------|----------|----------|----------|---------------------|------|-----|
|          |      | L         | W        | H        | D1       | D2       | A                   | B    | C   |
| SZD55C   | 1206 | 3.2±0.2   | 1.5±0.2  | 0.85±0.1 | 0.45±0.2 | 0.40±0.2 | 0.635               | 2.16 | 1.7 |
| SZD55B   | 1206 | 3.2±0.2   | 1.5±0.2  | 0.85±0.1 | 0.45±0.2 | 0.40±0.2 | 0.635               | 2.16 | 1.7 |
| SZD55C-S | 0805 | 2.0±0.2   | 1.25±0.2 | 0.85±0.1 | 0.35±0.2 | 0.35±0.2 | 0.508               | 1.22 | 1.4 |
| SZD55B-S | 0805 | 2.0±0.2   | 1.25±0.2 | 0.85±0.1 | 0.35±0.2 | 0.35±0.2 | 0.508               | 1.22 | 1.4 |




#### DEVICES OUTLOOK

Front side



Back side



SINLOON®

貼片型穩壓二極管

Surface Mount Zener Diode

SZD55C - 0805/1206

Voltage Range: 0.5W 4.7V ~ 36V (±5%)

□ ELECTRICAL CHARACTERISTICS b (Tamb = 25°C)

| SERIES                                     | SZD55C         | SZD55B     | SZD55C-S   | SZD55B-S   |
|--------------------------------------------|----------------|------------|------------|------------|
| Size Code in inch (mm)                     | 1206(3216)     | 1206(3216) | 0805(2012) | 0805(2012) |
| Zener Voltage Tolerance                    | ±5%            | ±2%        | ±5%        | ±2%        |
| Operating Temperature                      | -55°C ~ +125°C |            |            |            |
| Power Dissipation (P <sub>tot</sub> )      | 500mW          |            |            |            |
| Forward Voltage at 200mA (V <sub>F</sub> ) | 1.5V           |            |            |            |

□ ELECTRICAL DATA (±5% Zener Voltage Tolerance)

| Part Number |            | Device Marking Code | Nominal Zener Voltage V <sub>Z</sub> @I <sub>ZT</sub> |         | Max. Zener Impedance             |    |                                  |    | Max. Reverse Leakage Current   |     |
|-------------|------------|---------------------|-------------------------------------------------------|---------|----------------------------------|----|----------------------------------|----|--------------------------------|-----|
| (1206) ±5%  | (0805) ±5% |                     | V <sub>Z</sub> @I <sub>ZT</sub>                       |         | V <sub>ZT</sub> @I <sub>ZT</sub> |    | V <sub>ZT</sub> @I <sub>ZT</sub> |    | I <sub>R</sub> @V <sub>R</sub> |     |
| SZD55C      | SZD55C-S   | Voltage             | Min.(Vol.)                                            | Max.(V) | Ω                                | mA | Ω                                | mA | μA                             | V   |
| SZD55C4V7   | SZD55C4V7S | 4V7                 | 4.61                                                  | 4.79    | 70                               | 5  | 600                              | 1  | 0.5                            | 1   |
| SZD55C5V1   | SZD55C5V1S | 5V1                 | 4.85                                                  | 5.36    | 50                               | 5  | 550                              | 1  | 0.1                            | 1   |
| SZD55C5V6   | SZD55C5V6S | 5V6                 | 5.32                                                  | 5.88    | 30                               | 5  | 450                              | 1  | 0.1                            | 1   |
| SZD55C6V2   | SZD55C6V2S | 6V2                 | 5.89                                                  | 6.51    | 10                               | 5  | 200                              | 1  | 0.1                            | 2   |
| SZD55C6V8   | SZD55C6V8S | 6V8                 | 6.46                                                  | 7.14    | 8                                | 5  | 150                              | 1  | 0.1                            | 3   |
| SZD55C7V5   | SZD55C7V5S | 7V5                 | 7.13                                                  | 7.88    | 7                                | 5  | 50                               | 1  | 0.1                            | 5   |
| SZD55C8V2   | SZD55C8V2S | 8V2                 | 7.79                                                  | 8.61    | 7                                | 5  | 50                               | 1  | 0.1                            | 6.2 |
| SZD55C9V1   | SZD55C9V1S | 9V1                 | 8.65                                                  | 9.56    | 10                               | 5  | 50                               | 1  | 0.1                            | 6.8 |
| SZD55C10    | SZD55C10S  | 10                  | 9.50                                                  | 10.50   | 15                               | 5  | 70                               | 1  | 0.1                            | 7.5 |
| SZD55C11    | SZD55C11S  | 11                  | 10.45                                                 | 11.55   | 20                               | 5  | 70                               | 1  | 0.1                            | 8.2 |
| SZD55C12    | SZD55C12S  | 12                  | 11.40                                                 | 12.60   | 20                               | 5  | 90                               | 1  | 0.1                            | 9.1 |
| SZD55C13    | SZD55C13S  | 13                  | 12.35                                                 | 13.65   | 26                               | 5  | 110                              | 1  | 0.1                            | 10  |
| SZD55C15    | SZD55C15S  | 15                  | 14.25                                                 | 15.75   | 30                               | 5  | 100                              | 1  | 0.1                            | 11  |
| SZD55C16    | SZD55C16S  | 16                  | 15.20                                                 | 16.80   | 40                               | 5  | 170                              | 1  | 0.1                            | 12  |
| SZD55C18    | SZD55C18S  | 18                  | 17.10                                                 | 18.90   | 50                               | 5  | 170                              | 1  | 0.1                            | 13  |
| SZD55C20    | SZD55C20S  | 20                  | 19.00                                                 | 21.00   | 55                               | 5  | 220                              | 1  | 0.1                            | 15  |
| SZD55C22    | SZD55C22S  | 22                  | 20.90                                                 | 23.10   | 55                               | 5  | 220                              | 1  | 0.1                            | 16  |
| SZD55C24    | SZD55C24S  | 24                  | 22.80                                                 | 25.20   | 80                               | 5  | 220                              | 1  | 0.1                            | 18  |
| SZD55C27    | SZD55C27S  | 27                  | 25.65                                                 | 28.35   | 80                               | 5  | 220                              | 1  | 0.1                            | 20  |
| SZD55C30    | SZD55C30S  | 30                  | 28.50                                                 | 31.50   | 80                               | 5  | 220                              | 1  | 0.1                            | 22  |
| SZD55C33    | SZD55C33S  | 33                  | 31.35                                                 | 34.65   | 80                               | 5  | 220                              | 1  | 0.1                            | 24  |
| SZD55C36    | SZD55C36S  | 36                  | 34.20                                                 | 37.80   | 80                               | 5  | 220                              | 1  | 0.1                            | 27  |

◎ Device marking as zener voltage code & cathode terminal.

SINLOON®

貼片型穩壓二極管

Surface Mount Zener Diode

SZD55C - 0805/1206

Voltage Range: 0.5W 4.7V ~ 36V (±5%)

## Typical Characteristics ( $T_{amb} = 25^{\circ}\text{C}$ , unless otherwise specified)

Fig1. Thermal Resistance vs. Lead Length




Fig 4. Typical Change of Working Voltage vs. Junction Temperature




Fig2. Total Power Dissipation vs. Ambient Temperature




Fig5. Temperature Coefficient of V\_Z vs. Z-Voltage




Fig3. Typical Change of Working Voltage under Operating Conditions at  $T_{amb}=25^{\circ}\text{C}$





Fig 6. Diode Capacitance vs. Z-Voltage



SINLOON®

貼片型穩壓二極管

Surface Mount Zener Diode

SZD55C - 0805/1206

Voltage Range: 0.5W 4.7V ~ 36V (±5%)

□ Typical Characteristics (  $T_{amb} = 25^{\circ}\text{C}$  , unless otherwise specified )

Fig 7. Forward Current vs. Forward Voltage




Fig 9. Z-Current vs. Z-Voltage




Fig 8. Z-Current vs. Z-Voltage




Fig 10. Differential Z-Resistance vs. Z-Voltage





Fig 11. Thermal Response



SINLOON®

貼片型穩壓二極管

Surface Mount Zener Diode

SZD55C - 0805/1206

Voltage Range: 0.5W 4.7V ~ 36V (±5%)

□ Typical Characteristics (  $T_{amb} = 25^{\circ}\text{C}$  , unless otherwise specified )

Suggested thermal profiles for soldering processes




Fig.1 Typical Wave Soldering Thermal Profile




Fig.2 Typical IR Reflow Soldering Thermal Profile

SINLOON®

貼片型穩壓二極管

Surface Mount Zener Diode

SZD55C - 0805/1206

Voltage Range: 0.5W 4.7V ~ 36V (±5%)

PACKAGE SPECIFICATION

| Type     | Size | Quantity(ea)    |         |         |          | Gross Weight | SINLOON® |
|----------|------|-----------------|---------|---------|----------|--------------|----------|
|          |      | Paper Reel Tape | In Box  | Carton  |          |              |          |
| SZD55C   | 1206 | 5,000 Pcs       | 7" Reel | 50K pcs | 300K pcs | 13 Kgs       |          |
| SZD55B   | 1206 | 5,000 Pcs       | 7" Reel | 50K pcs | 300K pcs |              |          |
| SZD55C-S | 0805 | 5,000 Pcs       | 7" Reel | 50K pcs | 300K pcs | 10.5 kgs     |          |
| SZD55B-S | 0805 | 5,000 Pcs       | 7" Reel | 50K pcs | 300K pcs |              |          |

Fig-1: Figure




Fig-2: Q'ty: 5K/Reel





Fig-4 Q'ty: 300K / Carton.



Fig-3 Q'ty: 50K/ Inner Box



美隆電子產品規格特性參數的改變和更新不會另行通知。

Mayloon characteristic parameters of electronic product specification changes or updates without prior notice .