

SINLOON®

微波感應開關 TCZ3804 TCZ3800R TCZ9800R 系列

Microwave sensor switch - TCZ38004 TCZ3800R TCZ9800R

產品外型 Appearance			
型號 Model No.	TCZ3804	TCZ3800R	TCZ9800R
電壓 AC Voltage	AC220V 50/60Hz	AC220V 50/60Hz	AC220V 50/60Hz
可控負載 Loading	LED ≤ 100W ≤ 5 Lamp	LED ≤ 100W ≤ 3 Lamp	LED ≤ 100W ≤ 3 Lamp
待機功耗 Power consumption	≤ 1W (Standby)	≤ 1W (Standby)	≤ 1W (Standby)
頻率範圍 Frequency range	3.8GHz ±75MHz ISM 波段	5.8GHz ±75MHz ISM 波段	5.8GHz ±75MHz ISM 波段
發射功率 Emitter power	<0.5mW	<0.5mW	<0.5mW
感應範圍 Detection zone	(直徑x高度) Ø10M - H5M	(直徑x高度) Ø12M - H6M	(直徑x高度) Ø12M - H6M
感應角度 Sensitive angle	吸頂安裝 Ceiling: 360° 掛牆安裝 Wall hanging: 160°		
啟動光照 Star lux	7 - 20 Lux	2Lux - 2000 Lux (可調/Adjustable)	全天候(可選) ≤ 2Lux/≤ 10Lux/≤ 30Lux
感應距離 Sensitive distance	3 - 5M (米)	1 - 8M (Max. 8M) (可調/Adjustable)	10%/50%/75%/100% (Max. 10M)(Adjustable)
延時時間 Time delayed	20±5secs	3secs/4Mins (可選/Adjustable)	3secs/4Mins (可選/Adjustable)
感應速度 Motion detection	0.5 - 3M/secs	0.5 - 3M/secs	6/30/secs; 3/5/15/30mins (可選/Adjustable)
安裝高度 Mounting height	5M Max.	6M Max.	6M Max.
環境溫度 Operating temperature	-20°C ~+45°C	-20°C ~+45°C	-20°C ~+45°C
IP 等級 IP Rating	IP20	IP20	IP20
尺寸 Size	L:67xW:32xH:24mm	Ø:100xH:40mm	Ø:100xH:40mm
包裝 Packing	10Pc/Box; 50Box/Carton	50Pc/Carton	50Pc/Carton
			