

SINLOON®

智能電源 + 微波感應開關

Smart power + Microwave sensor switch

Model: WY series

產品外型 Appearance			
型號 Model No.	WY020F	WY021F	WY032
電壓 AC Voltage	AC180-265V 50/60Hz	AC180-265V 50/60Hz	AC180-265V 50/60Hz
輸出電壓 Outout voltage	DC24V-82V	DC24V-82V	DC24V-82V
輸出電流 Outout current	210mA ±10mA (Customizable/可定制)	210mA ±10mA (Customizable/可定制)	210mA ±10mA (Customizable/可定制)
可控負載 Loading	8 - 24W	8 - 24W	8 - 24W
待機功耗 Power consumption	≤1W	≤1W	≤1W
頻率範圍 Frequency range	5.8GHz ±75MHz ISM 波段	5.8GHz ±75MHz ISM 波段	3.8GHz ISM 波段
發射功率 Emitter power	<0.5mW	<0.5mW	<0.5mW
感應範圍 Detection zone	∅12M x H:6M	∅12M x H:6M	∅10M x H:5M
感應角度 Sensitive angle	Ceiling: 360° Wall hanging: 160°	Ceiling: 360° Wall hanging: 160°	Ceiling: 360° Wall hanging: 180°
感應距離 Sensitive distance	50%/75%/100% Optiona Max.8M	10%/50%/100% Optiona Max.8M	3 - 5M
啟動光照 Star lux	7 - 20 Lux	75-200 Lux (Optional)	7 - 20Lux
延時時間 Time delayed	3sesc/45sesc/4Mins (Optional)	3sesc/45sesc/4Mins (Optional)	20 ±5 Secs
感應速度 Motion detection	0.5 - 3m/sesc	0.5 - 3m/sesc	0.5 - 3m/sesc
安裝高度 Mounting height	~6M Max.	~6M Max.	~5M Max.
環境溫度 Operating temperature	-20°C ~+45°C	-20°C ~+45°C	-20°C ~+45°C
尺寸 Size	L:69 x W:36 x H:31mm	∅68 x H:31mm	L:68 x W:32 x H:25mm
包裝 Packing	100pcs/1carton	100pcs/1carton	100pcs/1carton

■ 特性:

- 產品具備了紅外感測,光控裝置及自動光測功能.
- 採用紅外傳感探測到人體移動或動物時自動啟動開關.
- 有人環境下電源持續開啓至所有人離開30秒以後才關閉.
- 在探測範圍內紅外線感測人體或有動物走動即自動啟動開關.

■ 優點:

- 二次節能,無接觸點,使用壽命長,無污染,安全可靠.
- 不受環境溫度的變化影響感測靈敏度.
- 感測距離遠(~8米/可設定),性能穩定,抗干擾,不受外界影響.
- 大功率負載,可以選擇二綫,三綫和四綫,帶消防(XF)連接綫.

■ 人體感應燈 紅外線感應;微波感應

- ◇ 一燈多用:樓梯間,地下室或走廊等地.
- ◇ 動態感應智慧開關:感測範圍約4-6米,感應動態後會自動亮燈,燈光會在45秒(沒有動作干擾的情況下)自動熄滅.
- ◇ 節能省電:採用市電,環保省電.
- ◇ 柔光明亮:自然光,帶來恰到好處的光源.
- ◇ 微波感應,160度角偵測.
- ◇ 讓感應燈更加智慧,照亮家中每個角落.